R3-1500



| D Number of meals per service | 10-30 covers |
|-------------------------------------|--------------|
| Amount processed per | 0.3-1.5 kg |

SALES DESCRIPTION

The R3-1500 table-top cutter is ideal for grinding, mincing and kneading, as well as for making mousses, emulsions and smooth stuffings. It effortlessly performs even the lengthiest task in just a few minutes, consistently producing a flawless end product.

B TECHNICAL DESCRIPTION

R3-1500 table-top cutter. 230V/50Hz/1ph. Power: 650 W. Speed: 1,500 rpm. 3.7-l stainless-steel bowl with handle, plus bowl-base, smooth-edged, twin-blade assembly. 10-30 covers.

Select the options you want from the list in Section **F** overleaf.

| C TECHNICAL CHARACTERISTICS | |
|-----------------------------|--|
| Effective output | 650 W |
| Electrical data | 230V/50Hz/1ph 5.7 A – plug supplied |
| Speed | 1,500 rpm |
| Size (L x W x H) | 210 x 320 x 400 mm |
| Recyclability | 95% |
| Net weight | 13 kg |
| Reference | 22384 |

CE MARKING

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006, EN 12852, EN 60529-2000 - IP55 - IP34

PRODUCT CHARACTERISTICS

MOTOR UNIT

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 650 W
- Stainless-steel motor shaft
- Motor base made from heavy-duty composite material
- Magnetic safety system, thermal failsafe and motor brake
- Single speed 1,500 rpm
- Pulse function for greater cutting precision

CUTTER FUNCTION

- 3.7-I stainless-steel cutter bowl with handle for better grip
- Bowl-base blade assembly with two high-strength, stainless-steel, smooth-edged blades for homogeneous processing even for small amounts
- Central lid opening for adding liquid or solid ingredients during processing
- High heat- and shock-resistant see-through lid to monitor processing from start to finish
- All parts are dishwasher-safe and can easily be removed for cleaning

STANDARD ATTACHMENTS

- 3.7-I bowl with lid
- Blade assembly with two smooth-edged, stainless-steel blades and a detachable cap



R3-1500

F OPTIONAL ATTACHMENTS

- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27288
- Fine-serrated, twin-blade assembly for chopping herbs and grinding spices Ref. 27287
- Additional smooth-edged, twin-blade assembly Ref. 27286



G ELECTRICAL DATA

230 V / 50 Hz / 1 ph – power cord and plug supplied







