

Blixer® 5 V.V.



5.5 L

D

Number of 200-g portions per service



Amount processed per operation

0.5 – 3.5 kg

A

SALES DESCRIPTION

The Blixer 5 V.V. can turn small amounts of cooked or raw ingredients into texture-modified meals (soft, puréed or liquid) in next to no time.

B

TECHNICAL DESCRIPTION

Blixer 5 V.V. 230V/50Hz/1 ph. Power: 1,400 W. Variable speed: 300 – 3,500 rpm. 5.5-l stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3 – 18 portions (200 g).

Select the options you want from the list in Section F overleaf.

C

TECHNICAL CHARACTERISTICS

Effective output	1,400 W
Electrical data	230V/50Hz/1 ph 12 A – plug not supplied
Variable speed	300 – 3,500 rpm
Size (L x W x H)	280 x 350 x 500 mm
Recyclability	95 %
Net weight	24 kg
Reference	33173

MARKING

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000 - IP55 - IP34

E

PRODUCT CHARACTERISTICS

MOTOR UNIT

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 1,400 W
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe and motor brake
- Variable speed 300 – 3,500 rpm
- Pulse function for greater cutting precision

BLIXER® FUNCTION

- 5.5-l stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat- and shock-resistant see-through lid to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 5.5-litre bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

Blixer® 5 V.V.

F OPTIONAL ATTACHMENTS

- Additional bowl, blade assembly, lid and scraper arm unit – Ref. 27165
- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27180
- Additional fine-serrated, twin-blade assembly – Ref. 27155

G ELECTRICAL DATA

230V/50Hz/1 ph – power cord and plug supplied

