BLIXER 23



Number of 200 g portions :	20 to 75 portions
Quantity processed per operation	4 to 15 kg

A SALES FEATURES

Blixer 23 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 23. Three-Phase. Power 4500 W. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 23L stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 20 to 75 portions and more. Select all the options at the back page, **F** part.

C TECHNICAL DATA			
Output power	4500 Watts		
Electrical datas	Three phase No plug inclu	ıded	
Speeds	1500 and 30	1500 and 3000 rpm	
Dimensions (LxWxH)	700 x 600 x	700 x 600 x 1250 mm	
Rate of recyclability	95%		
Net weight	110 kg		
Supply	Amperage	Reference	
400V/50/3	20 Amp	51341	

STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006, EN 12852, EN 60529-2000



PRODUCT FEATURES

MOTOR BASE

- Induction direct drive motor for intensive use.
- Power 4500 Watts.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- 2 speeds: 1500 and 3000 rpm.
- Pulse function for a better cut precision.

CUTTER FUNCTION

- Removable and tiltable 23 litre bowl for effortless emptying and cleaning.
- Bowl-base blade assembly with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Stainless-steel construction for making cleaning easier.
- Timer from 0 to 15 minutes for a better preparation control.
- Transparent lid with bowl scraper to improve the end-product consistency and with a lid wiper to enable user to monitor processing.
- Opening in centre of lid for adding liquid or dry ingredients during processing.
- 3 retractable wheels making it easier to move the appliance in order to clean the surface.

INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels



BLIXER 23

Â

* N O T E

When the appliance is switched on, the current is several times greater than the nominal current.

"The switch-on current of appliances must be taken into account when determining the cross-section of the conductors and choosing the systems that protect against excess current, in order to avoid excessive voltage drops during the switch-on period and the untimely triggering of the protective device."

We advise you to use a protective device specific to the switching-on of asynchronous motors. In every case, you must comply with the legislation currently in force.

G

DRAWINGS & DIMENSIONS







