

BLIXER 45



45 L

A SALES FEATURES

Blixer 45 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 45. Three-Phase. Power 9000 W. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 45L stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 30 to 150 portions and more. Select all the options at the back page, **F** part.

C TECHNICAL DATA

Output power	9000 Watts	
Electrical datas	Three phase No plug included	
Speeds	1500 and 3000 rpm	
Dimensions (LxWxH)	760 x 600 x 1400 mm	
Rate of recyclability	95%	
Net weight	138 kg	
Supply	Amperage	Reference
400V/50/3	40 Amp	53341

STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000

**D**

Number of 200 g portions :	30 to 150 portions
Quantity processed per operation	6 to 30 kg

E PRODUCT FEATURES**MOTOR BASE**

- **Induction direct drive motor** for intensive use.
- Power 9000 Watts.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- **2 speeds : 1500 and 3000 rpm.**
- Pulse function for a better cut precision.

CUTTER FUNCTION

- **Removable and tiltable 45 litre bowl** for effortless emptying and cleaning.
- **Bowl-base blade assembly** with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- **Stainless-steel construction** for making cleaning easier.
- **Timer from 0 to 15 minutes** for a better preparation control.
- **Transparent lid with bowl scraper** to improve the end-product consistency and **with a lid wiper** to enable user to monitor processing.
- **Opening in centre of lid** for adding liquid or dry ingredients during processing.
- **3 retractable wheels** making it easier to move the appliance in order to clean the surface.

INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels

BLIXER 45



* N O T E

When the appliance is switched on, the current is several times greater than the nominal current.

“The switch-on current of appliances must be taken into account when determining the cross-section of the conductors and choosing the systems that protect against excess current, in order to avoid excessive voltage drops during the switch-on period and the untimely triggering of the protective device.”

We advise you to use a protective device specific to the switching-on of asynchronous motors. In every case, you must comply with the legislation currently in force.

G

DRAWINGS & DIMENSIONS

