



TECHNICAL DATA

| Wash tank temperature | 55 - 65°C |
|--|------------------------|
| Rinse water temperature (booster tank) | Minimum 82°C |
| Low tempe cut-out (thermostop) activated | Yes |
| Cycle times | 1. 60sec. 2. 90sec. |
| Water consumption | 2.8 litres |
| Tank capacity | 21 litres |
| Tank heating | 2.5 kW |
| Power supply | 425/50/3 |
| Booster loading | 6.2 kW |
| Total loading | 7.1 kW |
| Pump capacity | 0.7 kW |
| Loading height | 440 mm |
| Bench to bench - internal dimension | 628 mm |

PRODUCT ADVANTAGES


- Easy-to-use electronic controls with 2 cycles - 60 & 90 seconds
- Electronic temperature gauges
- Suitable for all dish & glass washing applications. Useable chamber height of 440mm. Able to wash 1/1 GN pans when using optional open ended tray racks
- Low 2.8 litres per cycle rinse volume dish / glasswasher with Rinse Pump to guarantee rinse volume and pressure
- Fully enclosed 4 sided hood design - avoiding loss of energy / steam
- Optimum hygienic deep drawn tank with coved corners (no welds) and SELF-CLEANING CYCLE


- · Stainless steel wash and rinse arm with patented WIDE ANGLE FAN nozzle to maximise wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- Includes chemical dispensers, fill hose, power lead & pump-out drain for quick & easy installation
- Includes 1 x plate rack & 1 x cutlery holder
- Back flow prevention device as standard to meet Watermark Approval & ATS 5200.101
- **MADE IN GERMANY**

* Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly. For corner operation we recommend to make the right side of the machine accessible for service. For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.


DIMENSIONAL DRAWING







Benches etc not included



860°