



## **TECHNICAL DATA**

Cycle times*	75 / 120 sec
Water consumption	1.9 l/rack
Tank capacity	8 litres
Tank heating	0.8 kW
Power supply	240 / 50 / 1 (415 / 50 / 3N)
Booster loading	
Standard	2.8 kW
Alternative	4.2 kW
Total loading	
Standard	3.2 kW   15A
Alternative	5.4 kW   15A
	(3ph)
Wash pump	0.6 kW   220 l/min
Rack size	400 x 400 mm
Loading height	315 mm
Noise level	62 dB (A)
Weight (gross / net)	64 / 58 kg


## **PRODUCT ADVANTAGES**

- Compact glasswasher: with an installation height of only 820 mm ideal for narrow places or with integrated reverse osmosis and an installation height of 815 mm ideal for undercounter installation
- VISIOTRONIC control: single button control with remaining time indicator together with text and graphic display
- 1.9 l rinsing: water consumption per cycle of only 1.9 I which results in a reduction of water, chemicals and energy consumption of 35 %
- CLIP-IN wash and rinse arms: wash and rinse arms can be removed with one hand and without any tools


- · Fully integrated for polish free washing
- Intelligent data documentation: automatic recording of important operational data and consumptions and indication on the display
- · USB-interface: comfortable download of operational data in form of a protocol via USB
- GENIUS-X<sup>2</sup> fine filter system: advanced filter system with prewash function reduces detergent consumption up to 35%
- Interlocked strainer: prevents operation without tank strainer
- · Hygiene programme: for removal of calcium carbonate and other deposits from wash chamber


For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

## **DIMENSIONAL DRAWING**



8





<sup>\*</sup>Thermostop quarantees required temperatures with cold water and / or 240 V connection, the actual cycle times extend accordingly