

Technical data sheet for

GAS GRIDDLE CONVECTION ELECTRIC OVEN RANGE 1200mm

GP8121GEC



- Overall Construction
- Galvanized steel chassis
- $\bullet \ \ Welded \ hob \ surround \ with \ 1.5mm \ 304 \ stainless \ steel \ bull \ nose$
- Splashback and hob sides 1.2mm 304 stainless steel
- \bullet Front panels and oven sides 0.9mm 304 stainless steel
- \bullet Full 0.9mm stainless steel storage cabinet on right hand side
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet

GRIDDLE

- 20mm thick machined top plates standard
- Optional ribbed plate sections
- Optional mirror finish hard chrome plates
- 2.5mm thick 304 stainless steel splash guards sides and rear $\,$
- 2.0mm thick grease channel
- Three 36MJ 3 bar even heat burners with dual thermostatic controls
- Full pilot and flame failure protection with piezo ignition $% \left(1\right) =\left(1\right) \left(1\right$
- Stainless steel grease drawer
- \bullet Overlapping finish at front and rear of plate for easy clean

OVEN

- Fully welded and vitreous enamelled oven liner
- GN 2x1 capacity with 4 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Cast iron even heat oven sole plate
- 6.5kW heating elements
- 100W heavy-duty motor
- 200mm diameter heavy-duty circulation fan
- Welded frame drop down door with heavy-duty spring hinge system
- 0.9mm 304 stainless steel door outer
- 1.0mm press formed vitreous enamelled door inner
- High density fibreglass insulated
- Stay cool stainless steel door handle with cast metal handle mounts
- · Supplied with two chrome wire oven racks

- Heavy-duty thermostatic gas griddle
- 20mm thick griddle plate
- Ribbed plate options
- Chromed mirror plate options
- Top weld sealed plates
- 108MJ thermostatic griddle burner system
- Separate left, centre, and right heat zones
- GN 2/1 6.6kW electric convection oven
- Drop down door
- Storage cabinet on right hand side
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular
- Low back model (GPL) available

Controls

- Large easy use control knobs heat resistant reinforced
- Easy view control settings on knobs

GRIDDLE

- Separate left, centre and right side heat zones
- Three 90-300°C thermostats
- Flame failure pilot burners
- Piezo ignition to each pilot burner

OVEN

- 50-320°C thermostatic control
- Indicator lights for power and heating

Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Plate is finished front and rear with overlap construction to remove cleaning traps
- Control service and gas conversion through front of unit
- Burner service requires plate removal
- Removable oven racking and sole plate
- Easy clean vitreous enamel oven and door inner
- Door hinge spring adjustable on unit (door outer removed)
- Door disengages for lift off removal and increased service access
- Access to all parts from front of unit

Technical data sheet for

GAS GRIDDLE CONVECTION ELECTRIC **OVEN RANGE 1200mm**

) Waldorf

Specifications

Burners

Three 36ML3 bar chromed steel burners - Griddle Individual pilot, flame failure and piezo ignition

Flements

4.5kW bottom heat element

2.0kW top heat element

Oven Fan Motor

100W

Gas power

108MJ/hr. 30kW

Electrical requirements

1 phase connection:

230-240Vac, 50/60hz, 1P+N+E, 27.7A

3 phase connection:

400-415Vac, 50/60hz, 3P+N+E

L1 9.4A

L2 9.4A

L3 9.0A

Plate

Cooking surface 1192mm x 530mm, 6318cm2

Oven Dimensions

Width 665mm

Depth 590mm

Height 385mm

Rack size 660mm x 540mm

Rack positions 4

Gas connection

R 3/4 (BSP) male

130mm from RH side, 32mm from rear, and 655mm from floor

Optional underside connection (refer specification drawing)

All units supplied with Natural and LP gas regulator

Electrical connection

369mm from RH side, 484mm from rear, and 150mm from floor

DIMENSIONS Width 1200mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm Incl. low back 970mm

NETT WEIGHT

220kg

PACKING DATA

1.36m3, 300kg

Width 1245mm

Depth 870mm Height 1255mm

GAS TYPES

Available in Natural gas and LP gas.

Please specify when ordering

Units supplied complete with gas type conversion kits

Other gas types on request

OPTIONS AT EXTRA COST

Joining caps


Castors


Plinth mounting

Ribbed plate options

Chromed plate options

GP8121GEC







MOFFRT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9202 6820 bgarcia@moffat.com.au

New Zealand Moffat Limited

Christchurch Telephone 03-389 1007 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz





ISO9001

igned and manufactured by

MOFFET:

ISO99001 All Waldorf products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.



In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

Printed in New Zealand © Copyright Moffat Limited Moffat/BH/6864



