



MX1LSTS-CF Roll-in Blast Chiller / Freezer

Remote condensing unit version

Standard Features

- Free standing roll in trolley unit
- Ergonomic touch screen controls
- 5 function home screen
- Manual use Soft Chill, Hard Chill, Soft Freeze, Hard Freeze and Self Adaptive I-Chilling
- 99 program cycles
- Favourites key shortcuts to the last 9 programs used
- Pre-chilling cycle key to maximise efficiency
- Multi-point core temperature probe
- Timer mode or continuous run
- · Automatic fan stop when opening the door
- Operator selectable de-icing cycle
- External and internal finish made of 304 stainless steel
- Supplied with 20mm insulated stainless steel floor and ramp
- Front frame with anti-condensation system
- Injected polyurethane foam insulation 80mm thick
- Assembly required

Please refer to Moffat price list for options and accessories


Technical data


	Capacity	1 x 1/1GN trolley (trolley not included)
	External dimensions	W 1080mm x D 960mm x H 2170mm
	Usable internal dimensions	W 650mm x D 790mm x H 1885mm (A1) W 650mm x D 820mm x H 1885mm (A2)
	Load capacity	80kg*
	Electrical connections	1P+N+E, 230-240V, 50/60Hz, 20A, 2.7kW
	Waste	Provide for a water runoff & trap to the selected waste point (B)
	Door configuration	Must be stated at time of order
	Nett weight	200kg
	Remote condensing unit version (remote condensing unit not included)	
	Remote condensing unit requirements - Refrigerant type R452A	
	Condensing capacity upright Blast Chiller/Freezer 1.6kW / 3.8kW / 7.1kW for the respective evaporation temperatures of -40/-20/-10°C	
	Remote condensing unit with pump down control	

^{*} Note - Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

Ambient temperature requirement +15°C — +43°C

Australia New Zealand moffat.com.au moffat.co.nz Moffat Pty Limited Moffat Limited 740 Springvale Road 45 Illinois Drive Mulgrave Izone Business Hub Victoria 3170 Rolleston 7675 Australia New Zealand Telephone +613-9518 3888 Telephone +64 3-983 6600 Facsimile +613-9518 3833 Facsimile +64 3-983 6660 vsales@moffat.com.au sales@moffat.co.nz







(A) Electrical supply

70 (F)

- De-icing waste (B)
- Liquid Line 1/2" (D)
- (D') Suction line 1"1/8 (CP) Control panel
- Distance from wall
- Floor drain (E)
- (P) Door height
- (DR) Ramp protusion (SG) Overall height
- (A1) Single access
- (A2) Pass through





Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values. In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice. © Copyright Moffat Ltd AN-FRI-S-1801

