



UMX1STS-CF Roll-in Blast Chiller / Freezer

Standard Features

- Ultra Compact Free standing roll in trolley unit
- Ergonomic touch screen controls integrated into the door
- 5 function home screen
- Manual use Soft Chill, Hard Chill, Soft Freeze, Hard Freeze and Self Adaptive I-Chilling
- 99 program cycles
- Favourites key shortcuts to the last 9 programs used
- · Pre-chilling cycle key to maximise efficiency
- Multi-point core temperature probe
- Timer mode or continuous run
- Automatic fan stop when opening the door
- Operator selectable de-icing cycle
- External and internal finish made of 304 stainless steel
- Supplied with 20mm insulated stainless steel floor and ramp
- Front frame with anti-condensation system
- Injected polyurethane foam insulation 80mm thick
- Supplied Assembled

Please refer to Moffat price list for options and accessories

Technical data


	Capacity	1 x 1/1GN trolley (trolley not included)	
	External dimensions	W 710mm x D 1070mm x H 2120mm	
	Usable internal dimensions	W 500mm x D 650mm x H 1860mm	
	Load capacity	80kg*	
	Electrical connections	1P+N+E, 230-240V, 50/60Hz, 20A, 2.7kW	
	Waste	Provide for a water runoff & trap to the selected waste point (B)	
	Door configuration	Must be stated at time of order	
	Nett weight	170kg	
	Remote condensing unit version (remote condensing unit not included)		
	Remote condensing unit requirements - Refrigerant type R452A		
	Condensing capacity upright Blast Chiller/Freezer 1.6kW / 3.8kW / 7.1kW for the respective evaporation temperatures of -40/-20/-10°C		
	Remote condensing unit with pump down control		
	Ambient temperature requirement +15°C — +32°C		


^{*} Note – Load capacities may vary depending on the thermal conductivity of the food being chilled, the thickness of product and container used

Australia moffat.com.au	New Zealand moffat.co.nz
Moffat Pty Limited	Moffat Limited
740 Springvale Road	45 Illinois Drive
Mulgrave	Izone Business Hub
Victoria 3170	Rolleston 7675
Australia	New Zealand
Telephone +613-9518 3888	Telephone +64 3-983 6600
Facsimile +613-9518 3833	Facsimile +64 3-983 6660
vsales@moffat.com.au	sales@moffat.co.nz




Dimensions





- (A) Electrical supply
- (B) De-icing waste
- (SG) Without housed unit
- (D) Liquid Line 3/8"
- (D') Suction line 1"1/8
- (CP) Control panel
- (F) Distance from wall
- (CU) Useful
- (DR) Ramp protusion

Alternative door opening configurations available



500 (CU)

Disclaimer: All unit capacities are based on subjective testing. Moffat accepts no liability for production values. In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice. © Copyright Moffat Ltd AN-FRI-S-1804



