

ITEM	Hoshizaki Undercounter Refrigerator					
MODEL	RTE-170SDA-GN					
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity:0.43kVA(1.9A)					
AMPERAGE	Rated 1.4A Starting 6.8A					
ELECTRIC CONSUMPTION	Motor 195W(Power Factor65%) Heater 193W Refrigeration 223W Defrost 200W					
HEAT REJECTION	300W					
POWER CORD	2.5m (Plug with Earth Wire)					
EFFECTIVE CAPACITY	412L					
OUTSIDE DIMENSIONS	W1660×D700×H815mm					
INSIDE DIMENSIONS	W1290×D527×H588mm					
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)					
INTERIOR	Stainless Steel, ABS Plastic					
INSULATION	Polyurethane Foam					
REFRIGERATION SYSTEM	Forced Air Circulation					
DEFROST SYSTEM	Glass Tube Heater					
COMPRESSOR	Hermetic 110W					
CONDENSER	Fin and Tube type, Air—cooled					
EVAPORATOR	Fin and Tube Type					
REFRIGERANT	R134a					
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from −6 to 12℃					
DEFROST CONTROL	Microprocessor controlled					
ELECTRIC CIRCUIT PROTECTION	10A Fuse, Earth Wire					
COMPRESSOR PROTECTION	Motor Protector					
LEG	Urethane (76mm DIA 115mm HIGH)					
WEIGHT	Net:103kg (Gross: Approx. **kg)					
PACKAGE	Carton (Wooden Pallet) 1735mm(W) x 780mm(D) x 990mm(H)					
ACCESSORIES	Shelf x 6, Rail x 12					
OPERATING CONDITIONS	Ambient Temperature:5-43°C Voltage Range:Rated Voltage±6%					
the receive the right to make changes in specifications and design without prior notice.						

- \*We reserve the right to make changes in specifications and design without prior notice.

  1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.

  Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow).
- The heat rejection is based on the reached pulldown temperature at ambient temperature of 43°C and power supply of 23°OV SOHz.
   The amperage and electric consumption are based on measurements at ambient temperature of 43°C and power supply of 23°OV 50°Hz.
- 3. The cabinet temperature range of -6 to 12°C is guaranteed at ambient temperature of 30°C.
- 4. Product Code: T040-D008

					and the second s	
*	*		****	DATE	DRAWING NO.	SYMBOL
APPROVED	DESIGNED	SYMBOL	DATE	7 2018.02.09	D21966	