



HOSHIZAKI














ITEM	Hoshizaki Drawer Type Undercounter Freezer
MODEL	FTC-90DEA-GN-2D
POWER SUPPLY	1 Phase 220—240V 50Hz Capacity: 0.78kVA (3.6A)
AMPERAGE	Rated: 3.0A
ELECTRIC CONSUMPTION	Motor: *W (Power Factor: *%) Heater: 356W Refrigeration: *W Defrost: 356W
HEAT REJECTION	*W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	160L
OUTSIDE DIMENSIONS	900mm (W) x 700mm (D) x 815mm (H)
INSIDE DIMENSIONS	530mm (W) x 533mm (D) x 588mm (H)
EXTERIOR	Stainless Steel, Galvanized Steel (Rear / Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic 315W
CONDENSER	Fin and Tube type, Air—cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R404A/200g
TEMPERATURE CONTROL	Microprocessor (Digital Temp Indication) Adjustable from -25 to -7°C
DEFROST CONTROL	Microprocessor Controlled
ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector
LEG	Urethane (76mm DIA, 115mm HIGH)
WEIGHT	82kg (Gross Approx. *kg)
PACKAGE	Carton 965mm (W) x 780mm (D) x 950mm (H)
OPERATING CONDITIONS	Ambient Temperature: 5-43°C

- 1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
- 2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 32° C and power supply of 230V 50Hz. The amperage and electric consumption are based on measurements at ambient temperature of 32°C and power supply of 230V 50Hz.

 3. The cabinet temperature range of -25 to -7° C is
- guaranteed at ambient temperature of 30°C. 4. Product code: T018-C834(For HL)