



ITEM	Hoshizaki Reach-in Refrigerator
MODEL	HRE-140B
POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.86kVA (3.80A)
AMPERAGE	Rated: 2.89A Starting: 12.6A
ELECTRIC CONSUMPTION	501W (Power Factor: 75%) (Except Drain Pan Heater 170W) Heater: 230W Defrost: 230W
HEAT REJECTION	940W
POWER CORD	2.3m (Continental Plug with Earth Wire)
EFFECTIVE CAPACITY	1379L
OUTSIDE DIMENSIONS	1400mm(W)× 850mm(D)× 2015mm(H)
INSIDE DIMENSIONS	1296mm(W)× 678mm(D)× 1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Rear, Bottom)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Off-Cycle
COMPRESSOR	Hermetic 315W (Motor Size)
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R134a/220g
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from 0 to 16° C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto-reset)
DRAIN EVAPORATING PAN	Stainless Steel, 170W
CASTER	Urethane (76mm DIA, 115mm high)
WEIGHT	164kg (Gross 189kg)
PACKAGE	Carton (Wooden Pallet) 1450mm(W)× 940mm(D)× 2100mm(H)
ACCESSORIES	Power Cord(UK Plug)
OPERATING CONDITIONS	Ambient Temperature: 5 - 43° C Voltage Range: Rated Voltage ±10%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and water connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 43° C.
3. The drain pan may overflow if the door is opened frequently or under highly humid conditions in the rainy or summer season.
4. Product Code : R004

HOSHIZAKI REACH-IN REFRIGERATOR HRE-140B

APPROVED SAKAI	CHECKED SUGIYAMA	DESIGNED NISHIO	DRAWN IGUCHI	SCALE 1/20	TRIGONOMETRY
ISHIGURO	NISHIO	2012.07.17	DATE	2007.02.06	DRAWING NO. D01066
APPROVED	DESIGNED	SYMBOL	DATE		SYMBOL 3