M2 PASSTHROUGH DISHWASHER





STANDARD FEATURES

60, 120 and 180 second cycles

Wash capacity of up to 1,080 plates per hour Compatible with 595mm to 640mm benchgaps Touchscreen controls with versatile Heads Up Display

1.0HP soft start wash pump

Dual chemical pumps

Assured rinse with break tank and booster pump Hands-free drainage system with sump and drain pump Two-stage stainless steel wash and drain filtration Heavy-duty stainless-steel construction and manifold Independent stainless-steel arms

Uprateable power options for rapid rinse recovery

1x 500mm dish rack (600 70028)

1x 500mm cup rack (600 70029)

1x cutlery container (C660503)

1x quick connection kit (all hoses and 1p/15A plugset)

SPECIFICATIONS

SI ECII ICATIONS	
A - Hot Water	
Temperature	65°C*
Connection	3/4" male, hose supplied
Pressure	100-500kPa
Flow	10L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.4L per cycle
_	

D - Drainage


Dro	nic	pump	flexi-h	ose	25mm
-----	-----	------	---------	-----	------


C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.75
Three phase	400-415	50	15	9.00

*Suitable for connection to low inlet water temp, flow and/or pressure supplies.

isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice











Dimensions	Machine	Packed
Width (mm)	730	760
Depth (mm)	710	820
Height (mm)	1530	1460
Weight (kg)	94	125
Volume (m3)		0.91

Water Quality	Min	Max
рН	7	8
TDS	1	135
CI-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

Corner Installation Notes:

- a. Machine should be installed so racks are pushed into the back of the machine.
- b. Allow 300mm clearance to front for service access.
- c. Splashback return to be no higher than 150mm.

Touchsreen Control:

- a. Bracket supplied with controls enables install either side, under bench or on wall.
- b. Consult Operator Manual for full details on correct installation.







